

EPC 12.1" Configuration

eTOP-EPC12 T- - - - -

Resolution, port isolation

- 30** 4:3 800x600
- 31** 4:3 800x600 2x(isol COM)
- 35** 4:3 1024x768

Memory

- 2G** 2GB DDR3
- 4G** 2x2GB DDR3

Storage

- SHD** Standard Hard Drive (320GB)
- 8PSD** 8GB Solid State Drive SLC 0°-70° C
- 16PSD** 16GB Solid State Drive SLC 0°-70°C
- 32PSD** 32GB Solid State Drive SLC 0°-70°C
- 32SSD** 32GB Solid State Drive MLC 0°-70°C
- 64SSD** 64GB Solid State Drive MLC -40-85°C
- 128SSD** 128GB Solid State Drive MLC 0°-70°C
- 2CFST** 2GB CFAST 0-70°C
- 4CFST** 4GB CFAST -40-85°C
- 8CFST** 8GB CFAST -40-85°C
- 16CFST** 16GB CFAST -40-85°C
- 32CFST** 32GB CFAST -40-85°C

Operating System

- XP** Windows XP Pro
- XPE** Windows XP Embedded
- WES2009** Windows Embedded Standard WES 2009 Label
- W732** Windows 7 PRO 32 bit
- WES7** Windows Embedded Standard 7
- WE7M** Windows Embedded 7- MultitouchWS7P Label 32 bit

Power supply

- blank** 24VDC
- A** 100-240VAC Power Adapter

Optional Modules

- blank** not supplied
- WIFI** Wifi Module Kit WLAN+ BLUETOOTH COMBO MODULE
- GSM** 3.5G Module Kit SIERRA:MC8090(SMS)

Jmobile Runtime PC

- blank** not supplied
- JMRT** Jmobile Runtime licence

